



COMPONENT DATA SHEET

Kelmar®
waterproofing systems

#151 AGGREGATE

Crumb Rubber

Description

#151 Aggregate is a reprocessed rubber-based aggregate used with KELMAR® Merdek System. #151 Aggregate is a consistent quality, flexible aggregate with excellent durability.

Typical Uses

- As an additive to the KELMAR® Merdek system for a cushion floor

Features

- 100% recycled
- Flexible
- Slip resistant

Limitations

- Concrete substrate must be clean, sound, dry and free from all contaminants detrimental to bond
- Surface and air temperatures MUST be between 10°- 32°C (50°- 90°F) during installation and initial cure

Application

- Applied with notched trowel or gauge rake
- Mix ratio (initial): 1.5 gallon #151 Aggregate per 2 gallons KELMAR® Merdek Basecoat
- Mix ratio may be adjusted for ease of application

Theoretical Coverage

- Varies based on mix ratio used

Physical Properties

- **Appearance:** black granules
- **Specific Gravity:** 1.14 +/- 0.03
- **Solubility in Water:** insoluble

Safety Precautions

Please refer to product Safety Data Sheet

R&D Technical Solutions Ltd.

7000 Davand Drive, Mississauga, ON L5T 1J5 Canada Tel: 905.795.9900 Toll Free: 800.387.5703 Fax: 905.795.9912

www.kelmar.com

www.rdsolutions.ca

Revision Date: January 31, 2017